

**NX25-120 &
NX25-240**

WITH



FILL-RITE®

ON →
OFF ←



THE INDUSTRY'S BEST

CONTINUOUS DUTY FUEL TRANSFER PUMP

Fill-Rite is proud to announce the newest extension of its continuous duty family with the release of the new nextec® Intelligence AC models. The NX25-120 and NX25-240 fuel transfer series allow fleet managers to fuel all day with less downtime due to short duty cycles or overheating. Our industry-leading pumps are equipped with a variable speed motor and Fill-Rite's exclusive nextec Intelligence technology for elite performance in harsh applications. Its low-profile, lightweight construction eases installation while still moving fuel more efficiently than the competition.

THE FUTURE OF FUEL TRANSFER IS HERE



nextec Intelligence - Predicts, Protects, Performs

	NX25 SERIES					
	NX25-120		NX25-240			
THREAD	NPT		NPT		BSPP	
MOUNTING	2" BUNG	FOOT	2" BUNG	FOOT	2" BUNG	FOOT
FLOW RATE	25 GPM* / 95 LPM*					
VOLTAGE	120V AC @ 60HZ		230V - 240V @ 50 or 60HZ			
INLET	1-1/4"	1"	1-1/4"	1"	1"	
OUTLET	1"					
AMPERAGE	3.5 FLA		1.8 FLA			
HORSEPOWER	1/3 HP					
COMPATIBLE FLUIDS	DIESEL, GASOLINE, BIODIESEL UP TO B20, E15, KEROSENE, MINERAL SPIRITS, METHANOL (UP TO 15%)					
DUTY CYCLE	CONTINUOUS DUTY FOR ALL-DAY FUEL TRANSFER					
WARRANTY	LIMITED LIFETIME WARRANTY**					
CERTIFICATIONS	UL/cUL		UL/cUL		CE, ATEX, IECEX	



Bung Mount Configuration



Foot Mount Configuration

Features & Benefits

- Continuous duty[†]**
Nonstop performance eliminates downtime, saving you time and money
- Remote on/off**
Remote switching capability for tall, above ground tanks
- Intelligent tones**
Simplify troubleshooting with audible tones that indicate when and where attention is needed
- Variable speed motor**
Pump actively adjusts its speed for optimal performance and improves suction lift
- Lightweight**
At less than 23 lbs.[‡], nextec provides a hassle-free and strain-free installation
- Auto power down**
After 20 minutes of inactivity the pump will turn itself off, reducing energy costs
- Magnetic switch**
Smooth operation and completely field replaceable
- Reduced vapor lock**
Keep your operation running in the harshest summer temperatures
- Slow down in bypass**
Reduce energy consumption and preserve the life of wetted components

*Adding accessories will affect flow rate, **Warranty details can be found at fillrite.com, [†]Rated continuous duty for fuel transfer, [‡]Pump only models are <23lbs

NX25_SS_02_22



FILL-RITE
 8825 Aviation Drive
 Fort Wayne, IN 46809
 (800) 634-2695
fillrite.com

