

V20

Next-Generation **Modular Vane Pump**
for stationary applications fueling large equipment

GPRO[®]

PROFESSIONAL GRADE
PERFORMANCE

20 | **76**
GPM | L/min

115V/230V
Dual Voltage Configurable



Delivering the
HIGHEST TOTAL VALUE
in a Professional Grade Fuel Transfer Pump

The GPRO V20 provides professional grade performance with almost 2X the pressure output than other comparable 20 GPM pumps. It's packed with exceptional design features that extend pump life, make maintenance a breeze, and provide the best return on your investment.

HIGHEST TOTAL VALUE

QUALITY

Built to withstand tough applications, backed by a 5-year warranty

CONFIGURABILITY

Quick-fit modular design for accessories to best suit pump footprint

DURABILITY

Lifetime corrosion-resistant, rain-proof tested

PERFORMANCE

High-pressure performance ideal for use with a hose reel, less sensitive to filter clogs

EASY MAINTENANCE

Field replaceable switch, replaceable motor (without violating UL certification), replaceable start/run capacitor

EASY INSTALLATION

Included tank adapter allows easy install. Integrated port for anti-siphon kit

SUPERIOR DESIGN

Leak-free O-ring connections, integrated check valve with higher ability to hold prime, top performance under vapor lock conditions

GREATER SUCTION LIFT than the competition:



18 ft of Gasoline
15 ft of Diesel

RELIABLE performance in a variety of power supply conditions



115±10%=
103.5 V to 126.5 V

230±10%=
207 V to 253 V

GREAT PLAINS INDUSTRIES



V20

Next-Generation **Modular Vane Pump**
for stationary applications fueling large equipment

GPRO®

PROFESSIONAL GRADE
PERFORMANCE



QUICK-FIT READY!

Quickly attach a filter, meter, or both to **customize your personal fuel station.**

Simple flanged, four-bolt connections with O-ring for leak-free, trouble-free installation!

Quick-Fit Accessories Sold Separately

- Quick-Fit Filter Adapter Kit includes modular adapter and filter
- Modular Fuel Meters available in Gallons or Litres

Add the Quick-Fit Modular Filter Kit



- Easy Installation: the only tool needed is a hex key (not included)



- Install the filter adapter in three optional positions



ADDITIONAL FEATURES:

- Dual voltage configurable (115V/230V)
- Thermal limiting device to prevent overheating for extended life
- Easy access to fuel strainer: five minutes to clean strainer without removing the pump from the tank
- Die-cast switch lever with positive stop to prevent broken switches
- Lockable nozzle holder with drip catch
- Extreme Temperature (XT) models are capable of operation in temperatures as low as -40°F (-40°C)
- Combo models pairing the V20 with our QM40 fuel meter are also available

SPECS (ALL MODELS)

Max. Flow Rate:	20 GPM 76 L/min	
Voltage, Input:	115V (AC) 60Hz, 230V (AC) 50/60Hz <i>Dual Voltage Configurable</i>	
Pump Technology:	Sliding Vane	
Motor HP:	0.50	
Duty Cycle:	30 min. on / 30 min. off	
Operating Pressure:	Up to 25 PSI (1.72 bar)	
Suction Pipe:	Not Included	
At Sea Level 70° F (21.1° C)	Suction Lift:	Up to 15 ft. (4.5 m)
	Discharge Lift:	15 ft. (4.5 m)
Pump Housing:	Cast Iron	
Warranty:	Five-Year Pump Warranty	

Refer to manual for wiring instructions



See Model Specs
on Data Sheet

